







904e+



		<b>904e+</b>
<b>ENGINE</b>		
Emissions		STAGE III-A (Tier 3)
Model		PERKINS / 1104D-44T (3055/2200)
Power		68 kW @ 2200 rpm
PTO Power		68 kW
Rated speed		2360±25 rpm
Number of cylinders - Cubic capacity		4 Cylinders / 4.4 liters
Aspiration		Turbocharger and Intercooler
Bore x Stroke		105 mm x 127 mm
Max Torque		393 Nm
Torque reserve		33%
<b>CLUTCH</b>		
Type		Dry, dual, mechanical control
Diameter		11.5" (292 mm)
Lining		Serametalic
<b>TRANSMISION</b>		
Type		Carraro 506-Up
Shifting		(F+R)x4x3
Gears forwards/reverse		12 forward / 12 reverse
Speed		1.50 – 31.50 km/hr
<b>PTO SHAFT</b>		
Type		Independent
Speed		540/540E rpm and Synchronized PTO
<b>HYDRAULICS</b>		
Type		Mechanical with draft
Three point linkage		Cat. 2 linkage with ball ends
Control		Position, draft and mixed
Lift capacity		3000 Kg
Operating Pressure		180 Mpa
Pump capacity		48.5 lt/min @ 2400 rpm
Remote valves		Standart 2 set Valves
<b>OTHER</b>		
Drive system		4 WD
Operating space		Rollbar / Cab
Steering		Hydrostatic
Service Brake		Hydraulic, oil-cooled, 5+5 plate disc brakes
Parking Brake		Mechanic
Front axle 2WD		45° turning angle
Front axle 4WD		40° turning angle - LSD
Rear axle		Mechanical diferantial locking
<b>Standart Ballast</b>		
Front Ballast		10 x 30Kg + 2 x 50Kg
Rear Ballast		6 x 50Kg
<b>DIMENSIONS</b>		
A-Length		4112 mm
B-Wheelbase		2327 mm
C-Front track width		1500-1900 mm
D-Rear track width		1500-1900 mm
E-Width		1990 mm
F-Ground clearence		545 mm
G-Ground clearence with Trailer		535 mm
H-Folded ROPS height		2700 mm
K-Distance from Muffler		2720 mm
L-Distance from front to axle axis		825 mm
M-Maximum Height		2720 mm
N-Distance from lowerlink ends to rear axle axis		960 mm
Standart Front Tyre	Front	320/85 R24
Standart Rear Tyre	Rear	460/85 R30
Tractor Weight (Unballast)	Rollbar	3200 Kg
	Cab	3380 Kg
<b>ROPS</b>		
Rollbar		YES
Cab		YES